

GENERAL INFORMATION

EMPRESS DRYBACK

STANDARDS	ISO/DIS 19322.2:2016 EN649	Heterogeneous PVC
SIZE		1219 x 184 mm 609,6 x 302,8 mm
THICKNESS	ISO 24346	2,5 mm
WEAR LAYER	ISO 24340	0,55 mm
INSTALLATION SYSTEM		Glue Down
ACOUSTIC PAD		N/A
BEVEL		Big Bevel
EMBOSSING		N/A
GLOSS LEVEL		4-7 degrees
QUANTITY		18 planks & tiles / box 55 boxes / pallet (planks) 66 boxes / pallet (tiles)
COVER AREA		4,04 m ² / box (planks) 3,34 m ² / box (tiles) 222,20 m ² / pallet (planks) 220,44 m ² / pallet (tiles)

PERFORMANCE

INFLAMMABILITY	EN1350-1 EN ISO 9239-1 EN ISO 11925-2	B _{fl} -s1
STAINING RESISTANCE	EN ISO 26987:2012	Class 0
COLOUR FASTNESS	EN ISO 105-B02	Grade 6
FUNGI RESISTANCE	ISO 846	Growth intensity 0
DIMENSIONAL STABILITY	ISO 23999	≤ 0,15 %
ACOUSTIC INSULATION	EN ISO 10140-3 ISO 717-2	N/A
RESIDUAL INDENTATION	EN 433	< 0,1 mm
CASTOR CHAIR	ISO 4918 EN 425:2002	Pass
FORMALDEHYDE EMISSION	EN 14041:2004	Class E1
SLIP RESISTANCE	EN 13893 DN 51130	DS R10
ELECTROSTATIC BEHAVIOR	EN 1815	Pass
REACH	EC N° 1907/2006	Pass
VOC EMISSION	FRENCH VOC REGULATION	A+
UNDERFLOOR HEATING		Yes, 27°C max.

CLASSIFICATION & GUARANTEE

CLASSIFICATION	ISO 10874 Light commercial ISO 10874 Domestic EN 685 Light commercial EN 685 Domestic	Class 33 
GUARANTEE	Domestic Light commercial Commercial	25 years 20 years 10 years

