

GENERAL INFORMATION

IMPERIAL LIGHT

STANDARDS	ISO/DIS 19322.2:2016 EN649	Heterogeneous PVC
SIZE		1220 x 228 mm
THICKNESS	ISO 24346	5,5 mm
WEAR LAYER	ISO 24340	0,55 mm
INSTALLATION SYSTEM		Click Unilin
ACOUSTIC PAD		1,0 mm 10*IXPE
BEVEL		Regular Bevel
EMBOSSING		EIR Embossing
GLOSS LEVEL		2-4 degrees
QUANTITY		10 planks / box 56 boxes / pallet
COVER AREA		2,78 m ² / box 155,77 m ² / pallet

PERFORMANCE

INFLAMMABILITY	EN1350-1 EN ISO 9239-1 EN ISO 11925-2	B _{fl} -s1
STAINING RESISTANCE	EN ISO 26987:2012	Class 0
COLOUR FASTNESS	EN ISO 105-B02	Grade 6
FUNGI RESISTANCE	ISO 846	Growth intensity 0
DIMENSIONAL STABILITY	ISO 23999	≤ 0,15 %
ACOUSTIC INSULATION	EN ISO 10140-3 ISO 717-2	Δ Lw 21DB
RESIDUAL INDENTATION	EN 433	< 0,1 mm
CASTOR CHAIR	ISO 4918 EN 425:2002	Pass
FORMALDEHYDE EMISSION	EN 14041:2004	Class E1
SLIP RESISTANCE	EN 13893 DN 51130	DS R10
ELECTROSTATIC BEHAVIOR	EN 1815	Pass
REACH	EC N° 1907/2006	Pass
VOC EMISSION	FRENCH VOC REGULATION	A+
UNDERFLOOR HEATING		Yes, 27°C max.

CLASSIFICATION & GUARANTEE

CLASSIFICATION	ISO 10874 Light commercial ISO 10874 Domestic EN 685 Light commercial EN 685 Domestic	Class 33 
GUARANTEE	Domestic Light commercial Commercial	25 years 20 years 10 years



Container Orders Only.