

SOLID CORE BOARDS

Transforming ideas into reality

GENERAL INFORMATION

STANDARDS	PVC Co-extruded Foam Core
SIZE	900 x 2400 mm 900 x 2800 mm
THICKNESS	8,0 mm
INSTALLATION SYSTEM	Tongue & Groove (T&G) / Glue
SURFACE	0.14 mm PVC Film 0.40 mm PET Film
ADHESIVE	PUR hot

PERFORMANCE

FIRE RESISTANCE	EN 13501-1:2018 ASTM E84-20	Class B1 (c-s3,0,t1)
RESISTANCE TO HEAT		Temperature/ Heat up to 60°C
SCALE FORMATION		Low Susceptibility to hard water
CHEMICAL RESISTANCE		Caustics, Mineral Oil, Milk, Coffee
IMPACT RESISTANCE	EN 13245-1:2004	Pass
RESISTANCE TO LIGHT		Pass
RESIDUAL INDENTATION		Pass
RADIANT PANEL		Pass
DENSITY		0.75

GUARANTEE

GUARANTEE	Domestic Commercial	10 years 5 years
-----------	------------------------	---------------------

DIMENSIONS (MM)	SQM/ BOX	PCS/ BOX	WEIGHT/ BOX (KG)	BOXES/ PALLET	SQM/ PALLET	WEIGHT/ PALLET (KG)	PALLET SIZE (MM)
900 x 2400 x 8	2.16	2 pcs	28.08 kg	45	194.40	1263.60	2420 x 920 x 1140
900 x 2800 x 8	2.52	2 pcs	32.76 kg	45	226.80	1474.20	2820 x 920 x 1140